

# 4-ZONE ELECTRIC GLASS-CERAMIC COOKER - TOP VERSION

Project .....  
Rev.: .....  
Zone: .....  
Location: .....



CODICE  
CR0855839

MODELLO  
6NPC/1722

SERIE  
SERIE 600

## GENERAL CHARACTERISTICS

A line of small-sized cooking equipment designed for those who, even in small spaces, do not want to give up great performance. Made of AISI 304 18/10 stainless steel, finely finished with Scotch Brite satin finish, it has rounded edges and large capacity enclosures; it has 600/650 mm depth and modular width of 400/600/700/800/1000 mm; the series is completed by open, armored or refrigerated base supports.

The equipment is easily modular to one another until it forms a compact, gap-free whole thanks to a leak-covering profile that provides protection against leakage and thus maximum hygiene. High chimneys, ergonomic knobs mounted on a sloping dashboard for easy visibility, give the range ease of use from the first approach.

All models are CE approved.



## TECHNICAL SPECIFICATIONS

Kitchens with glass-ceramic countertops are available with 2 or 4 cooking zones that are marked with a circular screen print. The energy controller allows you to set the temperature, and an indicator lamp signals any residual heat on the top.

Static or ventilated GN 1/1 electric oven with adjustable temperature from 110-280°C.

4-ZONE ELECTRIC GLASS-CERAMIC COOKER - TOP  
VERSION

Project .....  
Rev.: .....  
Zone: .....  
Location: .....



CODICE  
CR0855839

MODELLO  
6NPC/I722

SERIE  
SERIE 600

Technical Information

SPECIFICATION	DATA
MATERIAL	CR0855839
DEFINITION	IRRAGGIAMENTO 4 Z.60 M70 6NPC/I722
COMMERCIAL LINE	SERIE 600
SUPPLY	ELECTRICS
DIM. WIDTH	700 mm
DIM. PRODUCTIVITY	600 mm
DIM. HEIGHT	295 mm
NET WEIGHT	12.3 Kg
VOLUME (net)	0.124
PACKAGE LENGTH	750 mm
PACKAGE WIDTH	750 mm
PACKAGING HEIGHT	250 mm
PACKAGE VOLUME	0,141 m3
GROSS PACKING WEIGHT	21 Kg
STANDARD POWER SUPPLY	380-415V 3N
FREQUENCY	50-60 Hz
ELECTRICAL POWER	8 kW
IP GRADE	IPX4
CERTIFIED MODEL	6NPC/I722

# 4-ZONE ELECTRIC GLASS-CERAMIC COOKER - TOP VERSION

Project .....  
Rev.: .....  
Zone: .....  
Location: .....



CODICE  
CR0855839

MODELLO  
6NPC/I722

SERIE  
SERIE 600

SCHEMA DI INSTALLAZIONE - INSTALLATION DIAGRAM - INSTALLATIONSPLAN - SCHÉMA D'INSTALLATION -  
ESQUEMA DE INSTALACION - INSTALLATIESCHEMA - IINSTALLATIONSRTNINGAR

MISURE IN mm - DIMENSIONS IN mm - ABMESSUNGEN IN mm  
MESURES EN mm - MEDIDAS EN mm - MATEN IN mm



## LEGENDA - LEGENDE - KEY - LEGENDE - LEYENDA - LEGENDA

E Pressacavo entrata linea elettrica - Stopfbuchse - Electric cable stress relief - Presse etoupe de cable el Pisacable - Elektrische kabelwartel

## 4-ZONE ELECTRIC GLASS-CERAMIC COOKER - TOP VERSION

Project .....  
Rev.: .....  
Zone: .....  
Location: .....




CODICE  
CR0855839

MODELLO  
6NPC/1722

SERIE  
SERIE 600

# PRODUCT'S RANGE PLUS



The glass-ceramic cookers are available in two versions: standard with a total output of 16.4 kW and enhanced with 18.4 kW in total.



The electric oven of GN 1/1 dimensions is equipped with armoured heating elements on the top and bottom with independent regulation and adjustable thermostat from 110 to 280°C.

Equipment is certified and compliant with the Low Voltage Directive 2014/35/EU according to the international CB scheme

