

REFRIGERATED BASE UNIT 4 DRAWERS - GAS R290A - TEMP. -2° + 8°

Project
Rev.:
Zone:
Location:



CODICE
SNR 40/2M-C2-C2

MODELLO
SNR 40/2M-C2-C2

SERIE
QUEEN 7

GENERAL CHARACTERISTICS

For those who do not want to give up the quality and solidity of a Queen stove, the Series 7 offers a 700 mm depth and more compact dimensions to fit any room, burners available in various configurations and wattages, enhanced by the refined Scotch Brite finish.

Thanks to its extreme compositional freedom, every composition is possible: you can combine Model i tops with accessorizable oven and neutral bases and hygienic finishes; create customized solutions by matching and attaching equipment back to back, sideways "flush" perfectly sealed, or "bridge" structures, offering high-level solutions that always perfectly meet the chef's needs. As a total guarantee, all equipment that make up a Queen7 kitchen are certified in compliance with international standards, including CE, GAR, AGA and others.



REFRIGERATED BASE UNIT 4 DRAWERS - GAS R290A - TEMP. -2° + 8°

Project
Rev.:
Zone:
Location:



CODICE
SNR 40/2M-C2-C2

MODELLO
SNR 40/2M-C2-C2

SERIE
QUEEN 7

TECHNICAL SPECIFICATIONS

GENERAL FEATURES

Exterior sides, back, doors and work surface made of stainless steel (Scotch-Brite satin finish).
Stainless steel outer bottom Fully radiused stainless steel inner lining.
Containment-molded inner bottom High-density polyurethane foam insulation (about 42 kg/m³) 50 mm thick, HCFC-free.
Copper-aluminum evaporating coil, cataphoresis painted with non-toxic epoxy resin.
Condensing coil made of painted iron with high thermal efficiency.
Anti-condensation heater, placed on the box under the magnetic gasket rebate.
Ergonomic handle on full width of door or drawer and magnetic gaskets on 4 sides.
Adjustable Ø 2" stainless steel feet H 150÷200 mm.

INTERIOR FITTINGS

Stainless steel uprights and guides, positioned interlocking to facilitate cleanability.
One pair of guides per on open cabinet.

REFRIGERATION UNIT

Ventilated evaporator to ensure maximum efficiency of the cooling system.
Compressor and condenser mounted on a removable base for easy and simple maintenance or replacement.
Environmentally friendly refrigerant fluid R290.
Automatic electric resistance defrosting device and condensate water evaporation system without electricity input.
Automatic evaporation of condensation water by means of electric resistance on prepared models.

CONTROLS, CONTROLS AND SAFETIES

Electronic teletermostat with temperature probe.
Automatically reset thermal protector to safeguard the compressor.

REFRIGERATED BASE UNIT 4 DRAWERS - GAS R290A - TEMP. -2° + 8°

Project
Rev.:
Zone:
Location:



CODICE
SNR 40/2M-C2-C2

MODELLO
SNR 40/2M-C2-C2

SERIE
QUEEN 7

Technical Information

SPECIFICATION	DATA
MATERIAL	SNR 40/2M-C2-C2
SUPPLY	ELECTRICS
DIM. WIDTH	1200 mm
DIM. PRODUCTIVITY	630 mm
DIM. HEIGHT	610 mm
GROSS PACKING WEIGHT	88 Kg
STANDARD POWER SUPPLY	220-240V 1N
ELECTRICAL POWER	0.348 kW
REFRIGERATION POWER	276
ENERGY CLASS	A

REFRIGERATED BASE UNIT 4 DRAWERS - GAS R290A - TEMP. -2° + 8°


Project
Rev.:
Zone:
Location:



CODICE
SNR 40/2M-C2-C2

MODELLO
SNR 40/2M-C2-C2

SERIE
QUEEN 7



REFRIGERATED BASE UNIT 4 DRAWERS - GAS R290A - TEMP. -2° + 8°

Project
Rev.:
Zone:
Location:



CODICE
SNR 40/2M-C2-C2

MODELLO
SNR 40/2M-C2-C2

SERIE
QUEEN 7

ACCESSORIES

CODE	MODELLO	DESCRIZIONE
BN0221700244	BN0221700244	REFRIGERATED BASE PROFILE M120 - TOP INSTALLATION 900 SERIES
BN0221700118	BN0221700118	REFRIGERATED BASE PROFILE M120 - TOP INSTALLATION 700 SERIES