

## CONTACT GRILL L400

Project .....  
Rev.: .....  
Zone: .....  
Location: .....



CODICE  
CR0856069

MODELLO  
6NCW/E400

SERIE  
SERIE 600

### GENERAL CHARACTERISTICS

A line of small-sized cooking equipment designed for those who, even in small spaces, do not want to give up great performance. Made of AISI 304 18/10 stainless steel, finely finished with Scotch Brite satin finish, it has rounded edges and large capacity enclosures; it has 600/650 mm depth and modular width of 400/600/700/800/1000 mm; the series is completed by open, armored or refrigerated base supports.

The equipment is easily modular to one another until it forms a compact, gap-free whole thanks to a leak-covering profile that provides protection against leakage and thus maximum hygiene. High chimneys, ergonomic knobs mounted on a sloping dashboard for easy visibility, give the range ease of use from the first approach.

All models are CE approved.



### TECHNICAL SPECIFICATIONS

The Contact grill is equipped with a group of AISI 304 electric heating elements powered by an oval section for direct cooking. GN 1/1 pan for the 400 model and GN 2/1 pan for the 800 model with humidifier function and removable grease collection for cleaning operations.

Temperature controlled by energy controller.

The heating element assembly is mounted on a tilting stand, held in the working or cleaning position by a locking pin. The cleaning of the firing surface is done by pyrolysis effect with the help of a rake appropriately shaped to the geometry of the heating elements.

The heating element assembly is mounted on a tilting stand, held in the working or cleaning position by a locking pin.

## CONTACT GRILL L400

Project .....  
Rev.: .....  
Zone: .....  
Location: .....



CODICE  
CR0856069

MODELLO  
6NCW/E400

SERIE  
SERIE 600

### Technical Information

SPECIFICATION	DATA
MATERIAL	CR0856069
DEFINITION	CUOCIWURSTEL EL.60 M40 6NCW/E400
COMMERCIAL LINE	SERIE 600
SUPPLY	ELECTRICS
DIM. WIDTH	400 mm
DIM. PRODUCTIVITY	600 mm
DIM. HEIGHT	295 mm
NET WEIGHT	23.4 Kg
VOLUME (net)	0,071
PACKAGE LENGTH	430 mm
PACKAGE WIDTH	690 mm
PACKAGING HEIGHT	500 mm
PACKAGE VOLUME	0,148 m3
GROSS PACKING WEIGHT	29 Kg
STANDARD POWER SUPPLY	380-415V 3N
FREQUENCY	50-60 Hz
ELECTRICAL POWER	4,080 kW
IP GRADE	IPX3
CERTIFIED MODEL	6NCW/E400

# CONTACT GRILL L400

Project .....  
Rev.: .....  
Zone: .....  
Location: .....




CODICE  
CR0856069

MODELLO  
6NCW/E400

SERIE  
SERIE 600

## SCHEMA DI INSTALLAZIONE - INSTALLATION DIAGRAM - INSTALLATIONSPLAN - SCHÉMA D'INSTALLATION - ESQUEMA DE INSTALACION - INSTALLATIESCHEMA - IINSTALLATIONSRTNINGAR

MISURE IN mm - DIMENSIONS IN mm - ABMESSUNGEN IN mm  
MESURES EN mm - MEDIDAS EN mm - MATEN IN mm



## LEGENDA - LEGENDE - KEY - LEGENDE - LEYENDA - LEGENDA

E Pressacavo entrata linea elettrica - Stopfbuchse - Electric cable stress relief - Presse etoupe de cable el Pisacable - Elektrische kabelwartel

## CONTACT GRILL L400

Project .....  
Rev.: .....  
Zone: .....  
Location: .....



CODICE  
CR0856069

MODELLO  
6NCW/E400

SERIE  
SERIE 600

# PRODUCT'S RANGE PLUS



Equipment is certified and  
compliant with the Low Voltage  
Directive 2014/35/EU according to  
the international CB scheme