

REFRIGERATED TABLE (4 DOORS TEMP -2/+8°C) TOP WITH SPLASHBACK

Project
Rev.:
Zone:
Location:



CODICE
BN26KK0212103LB

MODELLO
BOK04PA

SERIE
**REFRIGERATED
TABLES**

GENERAL CHARACTERISTICS

Baron refrigerated tables, all certified for efficiency and quality, guarantee the perfect observation of raw materials, processed delicatessen products, thanks also to an automatic door closing system with magnetic gasket.



TECHNICAL SPECIFICATIONS

Cell bottom printed with rounded corners and removable grid supports for the maximum degree of hygiene and load flexibility. Insulation thickness of 60 mm, made of high-density expanded polyurethane, completely free of CFC. Fully extractable drawers, thanks to special Fullterer telescopic guides in stainless steel. Self-closing door with 100° opening lock. Lower hinge fixed frontally for installation on the plinth.

REFRIGERATION UNIT

Evaporators positioned behind each door pillar to ensure uniform cold distribution

Evaporators with cathodic treatment

CONTROLS, MONITORING, AND SAFETY FEATURES:

Electronic control board with HACCP function

Hot gas defrost system (onboard motor versions)

Electric defrost (on predisposed versions)

Automatic evaporation device for condensate water without the need for electrical energy

REFRIGERATED TABLE (4 DOORS TEMP -2/+8°C) TOP WITH SPLASHBACK

Project
Rev.:
Zone:
Location:



CODICE
BN26KK0212103LB

MODELLO
BOK04PA

SERIE
**REFRIGERATED
TABLES**

Technical Information

| SPECIFICATION | DATA |
|-----------------------|-----------------|
| MATERIAL | BN26KK0212103LB |
| SUPPLY | ELECTRICS |
| DIM. WIDTH | 2195 mm |
| DIM. PRODUCTIVITY | 700 mm |
| DIM. HEIGHT | 950 mm |
| NET WEIGHT | 117 Kg |
| VOLUME (net) | 1.459675 |
| PACKAGE VOLUME | 1.781 m3 |
| GROSS PACKING WEIGHT | 137 Kg |
| STANDARD POWER SUPPLY | 220-240V 1N |
| FREQUENCY | 50Hz |
| ELECTRICAL POWER | 0.32 kW |
| GAS/REFRIGERANT TYPE | R134a |
| IP GRADE | IPX4 |
| CAPACITY | 492 |

REFRIGERATED TABLE (4 DOORS TEMP -2/+8°C) TOP WITH SPLASHBACK

Project
Rev.:
Zone:
Location:



CODICE
BN26KK0212103LB

MODELLO
BOK04PA

SERIE
REFRIGERATED
TABLES



REFRIGERATED TABLE (4 DOORS TEMP -2/+8°C) TOP WITH SPLASHBACK

Project
Rev.:
Zone:
Location:



CODICE
BN26KK0212103LB

MODELLO
BOK04PA

SERIE
REFRIGERATED
TABLES

PRODUCT'S RANGE PLUS



Evaporators placed behind each door pillar to ensure uniformity in cold distribution.



Ease of programming and immediate accessibility. The solution for quick and easy use.



Capacitor protected by filters to ensure optimal operation over time.



Molded cell bottom with rounded edges and removable grid supports for maximum hygiene and loading flexibility.



Full extension drawers with special Filterer stainless steel telescopic slides