

GN 1/1 PRESERVATION TABLE (2 DOORS TEMP -15/-20°C)

Project
Rev.:
Zone:
Location:



CODICE
BN26KK600210300

MODELLO
BOKPBT02

SERIE
**REFRIGERATED
TABLES**

GENERAL CHARACTERISTICS

Baron refrigerated tables, all certified for efficiency and quality, guarantee the perfect observation of raw materials, processed delicatessen products, thanks also to an automatic door closing system with magnetic gasket.



TECHNICAL SPECIFICATIONS

Cell bottom printed with rounded corners and removable grid supports for the maximum degree of hygiene and load flexibility. Insulation thickness of 60 mm, made of high-density expanded polyurethane, completely free of CFC. Fully extractable drawers, thanks to special Fuller telescopic guides in stainless steel. Self-closing door with 100° opening lock. Lower hinge fixed frontally for installation on the plinth.

REFRIGERATION UNIT

Equipped with a remote condensing unit

Evaporators positioned behind each door pillar to ensure uniform cold distribution

Evaporators with cathodic treatment

CONTROLS, MONITORING, AND SAFETY FEATURES:

Electronic control board with HACCP function

Electric defrost (on predisposed versions)

GN 1/1 PRESERVATION TABLE (2 DOORS TEMP -15/-20°C)

Project
Rev.:
Zone:
Location:



CODICE
BN26KK600210300

MODELLO
BOKPBT02

SERIE
**REFRIGERATED
TABLES**

Technical Information

SPECIFICATION	DATA
MATERIAL	BN26KK600210300
DEFINITION	BOKPBT02 -R452DX PSPD S/P C/PA BAR
DIM. WIDTH	1090 mm
DIM. PRODUCTIVITY	700 mm
DIM. HEIGHT	810 mm
NET WEIGHT	74 Kg
VOLUME (net)	0.61803
PACKAGE LENGTH	1140 mm
PACKAGE WIDTH	750 mm
PACKAGING HEIGHT	1060 mm
PACKAGE VOLUME	0,906 m3
GROSS PACKING WEIGHT	88 Kg
STANDARD POWER SUPPLY	220-240V 1N
FREQUENCY	50Hz
ELECTRICAL POWER	0.487 kW
GAS/REFRIGERANT TYPE	R452a
IP GRADE	IPX4
CAPACITY	246

GN 1/1 PRESERVATION TABLE (2 DOORS TEMP -15/-20°C)

Project
Rev.:
Zone:
Location:



CODICE
BN26KK600210300

MODELLO
BOKPBT02

SERIE
REFRIGERATED
TABLES



Remote unit connections:

- suction Ø8 m
- liquid Ø6 m



	Power cable position & length / Position und Länge des Speisekabels / Posizione e lunghezza cavo alim.
	Refrigerant tubes / Kälteleitungen / Tubi refrigerante
	Drainage pipe / Ablaufrohr / Tubo scarico
	Electrical components position / Position der elektrischen Komponente / Posizione componenti elettrici

OKP 2 DOORS GASTRONORM H 660

REFRIGERATED COUNTERS WITHOUT COOLING UNIT
KÜHLTISCHE OHNE KÜHLEINHEIT
TAVOLI REFRIGERATI PREDISPOSTI
TABLES REFRIGERES SANS GROUPE LOGE
MESAS REFRIGERADA SIN UNIDAD DE ENFRIAMIENTO

GN 1/1 PRESERVATION TABLE (2 DOORS TEMP -15/-20°C)

Project
Rev.:
Zone:
Location:



CODICE
BN26KK600210300

MODELLO
BOKPBT02

SERIE
REFRIGERATED
TABLES

PRODUCT'S RANGE PLUS



Ease of programming and immediate accessibility. The solution for quick and easy use.



Molded cell bottom with rounded edges and removable grid supports for maximum hygiene and loading flexibility.



The temperature uniformity throughout the refrigerated compartment is secured by a patented ventilation system using air channelling, aided by the absence of the evaporator in the compartment.



Full extension drawers with special Fuller stainless steel telescopic slides