

## GAS OVEN

Project .....  
Rev.: .....  
Zone: .....  
Location: .....



CODICE  
CR1018799

MODELLO  
Q90FO/G800

SERIE  
QUEEN 9

### GENERAL CHARACTERISTICS

It is the choice of those who need maximum strength and power. Queen9 is distinguished by its 900 mm depth, a 20/10-thick work surface, double-crown burners, and the use of elegant stainless steel with a Scotch Brite finish.

Details that not only offer maximum functionality and aesthetics, but also take into account the practical and ergonomic needs of those who work.

The extreme freedom of composition allows top models to be combined with accessorizable oven and neutral base units, even with hygienic finishes.

With more than 350 models immediately available in the catalog, Queen9 is already ready to start giving its best.

In addition, all equipment that makes up a Queen9 kitchen is certified in compliance with international standards, including CE, GAR, AGA and others.



### TECHNICAL SPECIFICATIONS

# GAS OVEN

Project .....  
Rev.: .....  
Zone: .....  
Location: .....



CODICE  
CR1018799

MODELLO  
Q90FO/G800

SERIE  
QUEEN 9

## Technical Information

SPECIFICATION	DATA
MATERIAL	CR1018799
DEFINITION	Q90FO/G800 BASE FORNO A GAS M80 PER TOP
COMMERCIAL LINE	QUEEN
SUPPLY	GAS
DIM. WIDTH	800 mm
DIM. PRODUCTIVITY	900 mm
DIM. HEIGHT	620 mm
NET WEIGHT	89.25 Kg
VOLUME (net)	0.446
PACKAGE LENGTH	1000 mm
PACKAGE WIDTH	840 mm
PACKAGING HEIGHT	640 mm
PACKAGE VOLUME	0,540 m3
GROSS PACKING WEIGHT	105 Kg
GAS POWER	8.5
GAS POWER (G25.3/25mbar)	8,50
CERTIFIED MODEL	Q90FO/G80

GAS OVEN

CODICE  
CR1018799


MODELLO  
Q90FO/G800

SERIE  
QUEEN 9

Project .....  
Rev.: .....  
Zone: .....  
Location: .....



MISURE IN cm - DIMENSIONS IN cm - ABMESSUNGEN IN cm- MESURES EN cm  
MEDIDAS EN cm - MATEN IN cm - DIMENSIONES EN cm



Legenda - Legende - Key - Légende - Leyenda - Legenda - Legenda	
<b>E</b> Pressacavo entrata linea elettrica - Stopfbuchse - Electric cable stress relief - Presse étoupe de câble él - Pisacable - Elektrische kabelwartel - Entrada cabo eléctrico	<b>G</b> Arrivo gas - Gasanschluss - Gas connection - Arrivée gaz - Union de gas - Gasaansluiting - Ligaç�o g�s <b>EN 10226-1 R 1/2; EN ISO 228-1 G 1/2 (DK)</b>
<b>S</b> Attacco scarico acqua - Wasserablauf - Water outlet - Vidange de l'eau - Desaguadero - Wateraftapaansluiting - Jun��o descarga �gua	<b>H20</b> Arrivo acqua - Wasseranschluss - Water inlet - Arriv�e eau - Union de �gua - Wateraansluiting - Jun��o alimenta��o �gua
<b>S1</b> Scarico vasca - Wannenabflussrohr - Pan outlet - Vidange du bac - Descarga cuba - Water toevoer - Descarga da cuba	<b>A1</b> = Calda - Heiss - Warm - Chaude - Caliente - Warm - Morno <b>A2</b> = Fredda - Kalt - Cold - Froid - Fria - Koude - Frio
<b>S2</b> Valvola di depressione - Anti-depression valve - Unterdruck ventil - Soupape de d�pression - V�lvula de d�presi��n - Onderdrukklep - V�lvula de depress��o	<b>L</b> Rubinetto di livello - Level tap - Wasserhahn - Robinet de niveau - Grifo de nivel - Niveaakraan - Torneira de nivel
<b>S3</b> Scarico acqua intercapedine - Wasserablauf Zwischenraum - Jacket water drain Evacuation eau double envelope - Descarga de �gua interst�cios - Afvoer water tussenruimte - Descarga de �gua na marmita com Sistema de aquecimento indirecto	
<b>S4</b> Scarico - Abflussrohr - Drain - Tuyau d��vacuation - Tubo de drenaje - Aftapbuis - Tubula���o de dreno	

## GAS OVEN

Project .....  
Rev.: .....  
Zone: .....  
Location: .....



CODICE  
CR1018799

MODELLO  
Q90FO/G800

SERIE  
QUEEN 9

# PRODUCT'S RANGE PLUS



Thanks to the jet-proofing certification (IPX5) obtained through specific tests, knobs and under-knobs can be washed at the end of the working day without compromising functionality and safety.



The front bar is a comfortable foothold for the cook; it keeps a safe distance from the worktop and thus protects against accidental collisions with what is resting on the worktops and at the same time the handles.