

ELECTRIC FRY TOP SMOOTH PLATE AISI 430 ON OPEN COMPARTMENT

Project
Rev.:
Zone:
Location:



CODICE
CR1350809

MODELLO
Q90FTV/E1203

SERIE
QUEEN 9

GENERAL CHARACTERISTICS

It is the choice of those who need maximum strength and power. Queen9 is distinguished by its 900 mm depth, a 20/10-thick work surface, double-crown burners, and the use of elegant stainless steel with a Scotch Brite finish.

Details that not only offer maximum functionality and aesthetics, but also take into account the practical and ergonomic needs of those who work.

The extreme freedom of composition allows top models to be combined with accessorizable oven and neutral base units, even with hygienic finishes.

With more than 350 models immediately available in the catalog, Queen9 is already ready to start giving its best.

In addition, all equipment that makes up a Queen9 kitchen is certified in compliance with international standards, including CE, GAR, AGA and others.



TECHNICAL SPECIFICATIONS

Cooking plate lowered from the plane by 4 cm and tilted 1 cm toward the front of the machine for grease drainage.

Large grease collecting drawer.

Available with soft iron plate or polished chrome plate.

High-power armored heating elements made of steels stainless steel.

Thermostatic safety control adjustable from 110 to 280°C for all versions.

Available in three versions:

- mild steel (for non-EU markets)
- in AISI 430
- in AISI 430

Plate welded to the hob that provides a larger cooking zone and eliminates dirt accumulation areas.

Plate with armoured incoloy heating elements placed under the bottom for cooking with temperature uniformity.

AISI430 plate.

Equipment certified for low voltage directive 2014/35/EU according to the international CB scheme.

Thanks to the jet-proofing certification (IPX5) obtained through specific tests, knobs and under-knobs can be washed at the end of the working day without compromising functionality and safety.

The front bar is a comfortable foothold for the cook; it keeps a safe distance from the worktop and thus protects against accidental collisions with what is resting on the worktops and at the same time the handles.

ELECTRIC FRY TOP SMOOTH PLATE AISI 430 ON OPEN COMPARTMENT

Project
Rev.:
Zone:
Location:



CODICE
CR1350809

MODELLO
Q90FTV/E1203

SERIE
QUEEN 9

Technical Information

| SPECIFICATION | DATA |
|-----------------------|--------------------------------------|
| MATERIAL | CR1350809 |
| DEFINITION | Q90FTV/E1203 FTE LISCIO M120 430 A/G |
| COMMERCIAL LINE | QUEEN |
| SUPPLY | ELECTRICS |
| DIM. WIDTH | 1200 mm |
| DIM. PRODUCTIVITY | 900 mm |
| DIM. HEIGHT | 870 mm |
| NET WEIGHT | 129 Kg |
| VOLUME (net) | 0.94 |
| PACKAGE LENGTH | 440 mm |
| PACKAGE WIDTH | 980 mm |
| PACKAGING HEIGHT | 500 mm |
| PACKAGE VOLUME | 0,980 m3 |
| GROSS PACKING WEIGHT | 143 Kg |
| STANDARD POWER SUPPLY | 380-415V 3N |
| FREQUENCY | 50-60 Hz |
| ELECTRICAL POWER | 22.5 kW |
| IP GRADE | IPX5 |
| CERTIFIED MODEL | Q90FTV/E1203 |

ELECTRIC FRY TOP SMOOTH PLATE AISI 430 ON OPEN COMPARTMENT

Project
Rev.:
Zone:
Location:



CODICE
CR1350809

MODELLO
Q90FTV/E1203

SERIE
QUEEN 9

SCHEMA DI INSTALLAZIONE - INSTALLATION DIAGRAM - INSTALLATIONSPLAN - SCHÉMA D'INSTALLATION - ESQUEMA DE INSTALACION - INSTALLATIESCHEMA - INSTALLATIONSRIJNINGAR

MISURE IN cm - DIMENSIONS IN cm - ABMESSUNGEN IN cm - MESURES EN cm
MEDIDAS EN cm - MATEN IN cm - DIMENSIONES EN cm



| Legenda - Legende - Key - Légende - Leyenda - Legenda - Legenda | |
|---|--|
| E Pressacavo entrata linea elettrica - Stopfbuchse - Electric cable stress relief - Presse étoupe de câble él - Pisacable - Elektrische kabelwartel - Entrada cabo eléctrico | G Arrivo gas - Gasanschluss - Gas connection - Arrivée gaz - Union de gas - Gasaansluiting - Ligação gás |
| S Attacco scarico acqua - Wasserablauf - Water outlet - Vidange de l'eau - Desaguadero - Wateraftapaansluiting - Junção descarga água | H20 Arrivo acqua - Wasseranschluss - Water inlet - Arrivée eau - Union de água - Wateraansluiting - Junção alimentação água |
| S1 Scarico vasca - Wannenabflussrohr - Pan outlet - Vidange du bac - Descarga cuba - Water toevoer - Descarga da cuba | A1 = Calda - Heiss - Warm - Chaude - Caliente - Warm - Morno |
| S2 Valvola di depressione - Anti-depression valve - Unterdruck ventili - Soupape de dépression - Válvula de depresión - Onderdrukkelep - Válvula de depressão | A2 = Fredda - Kalt - Cold - Froid - Fria - Koude - Frio |
| S3 Scarico acqua intercapedine - Wasserablauf Zwischenraum - Jacket water drain Evacuation eau double envelope - Descarga de água interstícios - Afvoer water tussenruimte - Descarga de água na marmitta com Sistema de aquecimento indirecto | |
| S4 Scarico - Abflussrohr - Drain - Tuyau d'évacuation - Tubo de drenaje - Aftapbuis - Tubulação de dreno | L Rubinetto di livello - Level tap - Wasserhahn - Robinet de niveau - Grifo de nivel - Niveaakraan - Torneira de nível |

ELECTRIC FRY TOP SMOOTH PLATE AISI 430 ON OPEN COMPARTMENT

Project
Rev.:
Zone:
Location:



CODICE
CR1350809

MODELLO
Q90FTV/E1203

SERIE
QUEEN 9

PRODUCT'S RANGE PLUS



Plate with armoured incoloy heating elements placed under the bottom for cooking with temperature uniformity.



A 10-mm tilt of the plates toward the front of the machine allows for optimal grease outflow to the grease pan.



Plate welded to the hob that provides a larger cooking zone and eliminates dirt accumulation areas.

ELECTRIC FRY TOP SMOOTH PLATE AISI 430 ON OPEN COMPARTMENT

Project
Rev.:
Zone:
Location:



CODICE
CR1350809

MODELLO
Q90FTV/E1203

SERIE
QUEEN 9

ACCESSORIES

| CODE | MODELLO | DESCRIZIONE |
|-----------|----------|---|
| CR0957610 | 90XFTP12 | SPLASH GUARD FOR FRY TOP MODULE 120 |
| CR0592079 | NXFTC4 | Fry top cleaning drawer M40-M120 |
| CR0592089 | NXFTC6/8 | Fry top cleaning drawer M40-M60-M80-M120 |
| CR1354989 | PRPC | Smooth plate cleaning scraper - chrome-plated |
| CR1356399 | RPR | Striped chrome plate scraper |
| CR1354999 | PKLR | Replacement blades (10PCS) |
| CR0592060 | NXFTT | PLANCHA CLEANING PLUG |