

# ELECTRIC FRYER 2 TANKS 15+15 L - WITH 2 BASKET KIT

Project .....  
Rev.: .....  
Zone: .....  
Location: .....



CODICE  
CR1018439T4W

MODELLO  
QT90FRI/E815-T4W

SERIE  
BARON 4.0

## GENERAL CHARACTERISTICS

From the solid foundation of Baron tradition, comes the new Queen 4.0 kitchen, even more practical, more accessorized, more technological.

An evolution in the field of professional kitchens.

Queen 4.0 is perfectly designed in detail to speed up and simplify every task of preparation, cooking, tidying up, and cleaning in the kitchen, and stand by you every day as a true ally in your work.



## TECHNICAL SPECIFICATIONS

Stainless steel outer coatings and feet.

Height of the work surface adjustable from 840 to 900mm.

Tops with a thickness of 2 mm.

AISI 18/10 stainless steel tanks with cold zone and foam expansion zone.

Oil drain taps.

Oil drip pans on request.

Safety thermostat (230°C) against excessive oil overtemperatures.

Heating by means of an AISI 304 stainless steel armoured heating element inside the tank and rotatable by more than 90° in the 22lt tank version.

Fully removable heating element in the 10 and 15-liter tank version.

The tanks have a large pouring area and a cold zone at the bottom to collect food particles and prolong the life of the oil.

Thanks to the jet-proofing certification (IPX5) obtained through specific tests, knobs and under-knobs can be washed at the end of the working day without compromising functionality and safety.

The front bar is a comfortable foothold for the cook; it keeps a safe distance from the worktop and thus protects against accidental collisions with what is resting on the worktops and at the same time the handles.

# ELECTRIC FRYER 2 TANKS 15+15 L - WITH 2 BASKET KIT

Project .....  
Rev.: .....  
Zone: .....  
Location: .....



CODICE  
CR1018439T4W

MODELLO  
QT90FRI/E815-T4W

SERIE  
BARON 4.0

## Technical Information

SPECIFICATION	DATA
MATERIAL	CR1018439T4W
DEFINITION	QT90FRI/E815-T4W FRIGG. EL.2V15+15LT M80
COMMERCIAL LINE	QUEEN
SUPPLY	ELECTRICS
DIM. WIDTH	800 mm
DIM. PRODUCTIVITY	900 mm
DIM. HEIGHT	870 mm
NET WEIGHT	114.8 Kg
VOLUME (net)	0.626
PACKAGE LENGTH	860 mm
PACKAGE WIDTH	1020 mm
PACKAGING HEIGHT	1150 mm
PACKAGE VOLUME	1,010 m3
GROSS PACKING WEIGHT	130 Kg
STANDARD POWER SUPPLY	380-415V 3N
FREQUENCY	50-60 Hz
ELECTRICAL POWER	26 kW
IP GRADE	IPX5
CAPACITY	15 litri
CERTIFIED MODEL	Q90FRI/E815

ELECTRIC FRYER 2 TANKS 15+15 L - WITH 2 BASKET  
KIT

Project .....  
Rev.: .....  
Zone: .....  
Location: .....



CODICE  
CR1018439T4W

MODELLO  
QT90FRI/E815-T4W

SERIE  
BARON 4.0

MISURE IN cm - DIMENSIONS IN cm - ABMESSUNGEN IN cm- MESURES EN cm  
MEDIDAS EN cm - MATEN IN cm - DIMENSIONES EN cm



Legenda - Legende - Key - Légende - Leyenda - Legenda - Legenda	
<b>E</b> Pressacavo entrata linea elettrica - Stopfbuchse - Electric cable stress relief - Presse étoupe de câble él - Pisacable - Elektrische kabelwartel - Entrada cabo eléctrico	<b>G</b> Arrivo gas - Gasanschluss - Gas connection - Arrivée gaz - Union de gas - Gasaansluiting - Ligação gás
<b>S</b> Attacco scarico acqua - Wasserablauf - Water outlet - Vidange de l'eau - Desaguadero - Wateraftapaansluiting - Junção descarga água	<b>H20</b> Arrivo acqua - Wasseranschluss - Water inlet - Arrivée eau - Union de água - Wateraansluiting - Junção alimentação água
<b>S1</b> Scarico vasca - Wannenabflussrohr - Pan outlet - Vidange du bac - Descarga cuba - Water toevoer - Descarga da cuba	<b>A1</b> = Calda - Heiss - Warm - Chaude - Caliente - Warm - Morno <b>A2</b> = Fredda - Kalt - Cold - Froid - Fria - Koude - Frio
<b>S2</b> Valvola di depressione - Anti-depression valve - Unterdruck ventil - Soupape de dépression - Válvula de depresión - Onderdrukklep - Válvula de depressão	<b>L</b> Rubinetto di livello - Level tap - Wasserhahn - Robinet de niveau - Grifo de nivel - Niveaakraan - Torneira de nivel
<b>S3</b> Scarico acqua intercapedine - Wasserablauf Zwischenraum - Jacket water drain Evacuation eau double envelope - Descarga de água interstícios - Afvoer water tussenruimte - Descarga de água na marmitta com Sistema de aquecimento indirecto	
<b>S4</b> Scarico - Abflussrohr - Drain - Tuyau d'évacuation - Tubo de drenaje - Aftapbuis - Tubulação de dreno	

# ELECTRIC FRYER 2 TANKS 15+15 L - WITH 2 BASKET KIT

Project .....  
Rev.: .....  
Zone: .....  
Location: .....



CODICE  
CR1018439T4W

MODELLO  
QT90FRI/E815-T4W

SERIE  
BARON 4.0

## PRODUCT'S RANGE PLUS



Data collection, operation monitoring, remote control are just some of the possibilities that connectivity puts at your disposal.



Thanks to the jet-proofing certification (IPX5) obtained through specific tests, knobs and under-knobs can be washed at the end of the working day without compromising functionality and safety.



The front bar is a comfortable foothold for the cook; it keeps a safe distance from the worktop and thus protects against accidental collisions with what is resting on the worktops and at the same time the handles.

# ELECTRIC FRYER 2 TANKS 15+15 L - WITH 2 BASKET KIT

Project .....  
Rev.: .....  
Zone: .....  
Location: .....



CODICE  
**CR1018439T4W**

MODELLO  
**QT90FRI/E815-T4W**

SERIE  
**BARON 4.0**

## ACCESSORIES

CODE	MODELLO	DESCRIZIONE
CR1357499	<b>4.0IOTPRO</b>	PRO Subscription - Cloud
CR1357479	<b>4.0IOTENTRY</b>	ENTRY Subscription - Cloud
CR1353969	<b>QCF22/23P</b>	STAINLESS STEEL BASKET FOR FRYERS 22/23P LT
CR1353979	<b>QCF22/23</b>	22/23 L STAINLESS STEEL BASKET FOR FRYERS
CR0997189	<b>9BRO</b>	OIL PAN
BN418031940080	<b>CF 12M</b>	FRYING TANK LID
BN418031940150	<b>GFF15</b>	BOTTOM GRID FRYER 15 L
BN418031940180	<b>CF15</b>	FRYER BASKET 15 L
BN418031940190	<b>CF15P</b>	SMALL BASKET FOR FRYER 15 LT