

2-ZONE INDUCTION COOKER PASS-THROUGH - ON CABINET

Project
Rev.:
Zone:
Location:



CODICE
CR1358829

MODELLO
N1100PCV/IND451

SERIE
SERIE GIANO

GENERAL CHARACTERISTICS

The Giano pass-through Series appliances are characterized by their great versatility, the perfect combination of modules, and their robustness, thanks to 2 mm thick laser-cut AISI 304 cooking surfaces.

These peculiarities make it possible to make firing blocks according to specific customer requirements.

Reliability and high efficiency are ensured by the use of tested components and the high efficiency of the heating elements used.

Support bases can be equipped with pass-through ovens, ventilated hot cabinets, neutral, or cantilevered or bridged.

Machines all complying with CE regulations.

RAL paint treatment can be requested.



TECHNICAL SPECIFICATIONS

Stainless steel outer coatings and Scotch Brite finish.

Tops with a thickness of 2 mm.

Contoured dashboards with controls angled toward the operator.

Unbreakable watertight glass-ceramic top.

Cooking zones marked with circular silk-screen printing 28 cm in diameter.

5 kW single zone power.

Device detects presence and anti-overheating device.

Heating activity indicator light.

2-ZONE INDUCTION COOKER PASS-THROUGH - ON CABINET

Project
Rev.:
Zone:
Location:



CODICE
CR1358829

MODELLO
N1100PCV/IND451

SERIE
SERIE GIANO

Technical Information

SPECIFICATION	DATA
MATERIAL	CR1358829
DEFINITION	N1100PCV/IND451 INDUZIONE M45 VANO G.
COMMERCIAL LINE	SERIE 1100 B
SUPPLY	ELECTRICS
DIM. WIDTH	450 mm
DIM. PRODUCTIVITY	1100 mm
DIM. HEIGHT	870 mm
NET WEIGHT	30 Kg
VOLUME (net)	0.431
PACKAGE LENGTH	510 mm
PACKAGE WIDTH	1280 mm
PACKAGING HEIGHT	1150 mm
PACKAGE VOLUME	0,751 m3
GROSS PACKING WEIGHT	52 Kg
STANDARD POWER SUPPLY	380-415V 3
FREQUENCY	50/60 Hz
ELECTRICAL POWER	10 kW
IP GRADE	IPX5
CAPACITY	26 litri
CERTIFIED MODEL	N1100PCV/IND451

2-ZONE INDUCTION COOKER PASS-THROUGH - ON
CABINET

CODICE	MODELLO	SERIE
CR1358829	N1100PCV/IND451	SERIE GIANO

Project
Rev.:
Zone:
Location:

