

REFRIGERATED TABLE (4 DOORS TEMP -2/+8°C)

Project
Rev.:
Zone:
Location:



CODICE
BN26KK021210376

MODELLO
BOK04

SERIE
**REFRIGERATED
TABLES**

GENERAL CHARACTERISTICS

Baron refrigerated tables, all certified for efficiency and quality, guarantee the perfect observation of raw materials, processed delicatessen products, thanks also to an automatic door closing system with magnetic gasket.



TECHNICAL SPECIFICATIONS

Cell bottom printed with rounded corners and removable grid supports for the maximum degree of hygiene and load flexibility. Insulation thickness of 60 mm, made of high-density expanded polyurethane, completely free of CFC. Fully extractable drawers, thanks to special Fuller telescopic guides in stainless steel. Self-closing door with 100° opening lock. Lower hinge fixed frontally for installation on the plinth.

REFRIGERATION UNIT

Evaporators positioned behind each door pillar to ensure uniform cold distribution

Evaporators with treatment in cataphoresis

CONTROLS, MONITORING, AND SAFETY FEATURES:

Electronic control board with HACCP function

Hot gas defrost system (onboard motor versions)

Electric defrost (on predisposed versions)

Automatic evaporation device for condensate water without the need for electrical energy

REFRIGERATED TABLE (4 DOORS TEMP -2/+8°C)

Project
Rev.:
Zone:
Location:



CODICE
BN26KK021210376

MODELLO
BOK04

SERIE
**REFRIGERATED
TABLES**

Technical Information

SPECIFICATION	DATA
MATERIAL	BN26KK021210376
DEFINITION	BOK04 R290DX TNN PSPDPSPD S/P BAR
DIM. WIDTH	2190 mm
DIM. PRODUCTIVITY	700 mm
DIM. HEIGHT	810 mm
NET WEIGHT	117 Kg
VOLUME (net)	1.24173
PACKAGE LENGTH	2240 mm
PACKAGE WIDTH	750 mm
PACKAGING HEIGHT	1060 mm
PACKAGE VOLUME	1,781 m3
GROSS PACKING WEIGHT	137 Kg
STANDARD POWER SUPPLY	220-240V 1N
FREQUENCY	50Hz
ELECTRICAL POWER	0.32 kW
GAS/REFRIGERANT TYPE	R134a
IP GRADE	IPX4
CAPACITY	492

REFRIGERATED TABLE (4 DOORS TEMP -2/+8°C)

Project
Rev.:
Zone:
Location:



CODICE
BN26KK021210376

MODELLO
BOK04

SERIE
REFRIGERATED
TABLES



REFRIGERATED TABLE (4 DOORS TEMP -2/+8°C)

Project
Rev.:
Zone:
Location:



CODICE
BN26KK021210376

MODELLO
BOK04

SERIE
REFRIGERATED
TABLES

PRODUCT'S RANGE PLUS



Evaporators placed behind each door pillar to ensure uniformity in cold distribution.



Ease of programming and immediate accessibility. The solution for quick and easy use.



Capacitor protected by filters to ensure optimal operation over time.



Molded cell bottom with rounded edges and removable grid supports for maximum hygiene and loading flexibility.



Full extension drawers with special Filterer stainless steel telescopic slides