

## 4-RING COOKER - TOP VERSION

Project .....  
Rev.: .....  
Zone: .....  
Location: .....



CODICE  
CR0855759

MODELLO  
6NPC/E700

SERIE  
SERIE 600

### GENERAL CHARACTERISTICS

A line of small-sized cooking equipment designed for those who, even in small spaces, do not want to give up great performance. Made of AISI 304 18/10 stainless steel, finely finished with Scotch Brite satin finish, it has rounded edges and large capacity enclosures; it has 600/650 mm depth and modular width of 400/600/700/800/1000 mm; the series is completed by open, armored or refrigerated base supports.

The equipment is easily modular to one another until it forms a compact, gap-free whole thanks to a leak-covering profile that provides protection against leakage and thus maximum hygiene. High chimneys, ergonomic knobs mounted on a sloping dashboard for easy visibility, give the range ease of use from the first approach.

All models are CE approved.



### TECHNICAL SPECIFICATIONS

Electric cookers have round cast iron plates hermetically fixed on the top and are 180 mm and 220 mm in diameter, with 1.5 and 2.6 kW power respectively.

Also available in upgraded versions with all 2.6 kW plates.

Static or ventilated GN 1/1 electric oven with adjustable temperature from 110-280°C.

## 4-RING COOKER - TOP VERSION

Project .....  
Rev.: .....  
Zone: .....  
Location: .....



CODICE  
CR0855759

MODELLO  
6NPC/E700

SERIE  
SERIE 600

### Technical Information

SPECIFICATION	DATA
MATERIAL	CR0855759
DEFINITION	4 PIASTRE EL.TONDE 60 M70 6NPC/E700
COMMERCIAL LINE	SERIE 600
SUPPLY	ELECTRICS
DIM. WIDTH	700 mm
DIM. PRODUCTIVITY	600 mm
DIM. HEIGHT	295 mm
NET WEIGHT	86.3 Kg
VOLUME (net)	0.124
PACKAGE LENGTH	650 mm
PACKAGE WIDTH	750 mm
PACKAGING HEIGHT	1150 mm
PACKAGE VOLUME	0,560 m3
GROSS PACKING WEIGHT	95 Kg
STANDARD POWER SUPPLY	380-415V 3N
FREQUENCY	50-60 Hz
ELECTRICAL POWER	8.2 kW
IP GRADE	IPX4
CERTIFIED MODEL	6NPC/E700

## 4-RING COOKER - TOP VERSION

Project .....

Rev.: .....

Zone: .....

Location: .....



baron


CODICE  
**CR0855759**

MODELLO  
**6NPC/E700**

SERIE  
**SERIE 600**

SCHEMA DI INSTALLAZIONE - INSTALLATION DIAGRAM - INSTALLATIONSPLAN - SCHÉMA D'INSTALLATION -  
ESQUEMA DE INSTALACION -INSTALLATIESCHEMA - IINSTALLATIONSRIITNINGAR

MISURE IN mm - DIMENSIONS IN mm - ABMESSUNGEN IN mm  
MESURES EN mm - MEDIDAS EN mm - MATEN IN mm



LEGENDA - LEGENDE - KEY - LEGENDE - LEYENDA - LEGENDA

E Pressacavo entrata linea elettrica - Stopfbuchse - Electric cable stress relief - Presse etoupe de cable el Pisacable - Elektrische kabelwarte

## 4-RING COOKER - TOP VERSION

Project .....  
Rev.: .....  
Zone: .....  
Location: .....



CODICE  
CR0855759

MODELLO  
6NPC/E700

SERIE  
SERIE 600

# PRODUCT'S RANGE PLUS



The plates are hermetically attached to the top, which has a vessel for collecting liquids and is completely smooth for easier cleaning.



The electric oven of GN 1/1 dimensions is equipped with armoured heating elements on the top and bottom with independent regulation and adjustable thermostat from 110 to 280°C.

Equipment is certified and compliant with the Low Voltage Directive 2014/35/EU according to the international CB scheme

