

# REFRIGERATED COUNTER GN 1/1 ( 2 DOORS TEMP -15/-20°C)

Project .....  
Rev.: .....  
Zone: .....  
Location: .....



CODICE  
**BN26WC500210376**

MODELLO  
**BOWBT02**

SERIE  
**REFRIGERATED  
TABLES**

## GENERAL CHARACTERISTICS

Baron refrigerated tables, all certified for efficiency and quality, guarantee the perfect observation of raw materials, processed delicatessen products, thanks also to an automatic door closing system with magnetic gasket.



## TECHNICAL SPECIFICATIONS

Cell bottom printed with rounded corners and removable grid supports for the maximum degree of hygiene and load flexibility. Insulation thickness of 60 mm, made of high-density expanded polyurethane, completely free of CFC. Fully extractable drawers, thanks to special Fullerer telescopic guides in stainless steel. Self-closing door with 100° opening lock. Lower hinge fixed frontally for installation on the plinth. Removable condensing unit.

### REFRIGERATION UNIT

Out-of-cell evaporator for greater loading convenience

Ducted ventilation system to even out internal temperature

Evaporators with treatment in cataphoresis

### CONTROLS, MONITORING, AND SAFETY FEATURES:

Electronic control board with HACCP function

Hot gas defrost system (onboard motor versions)

Electric defrost (on predisposed versions)

Automatic condensate evaporation device without the need for any electricity

# REFRIGERATED COUNTER GN 1/1 ( 2 DOORS TEMP -15/-20°C)

Project .....  
Rev.: .....  
Zone: .....  
Location: .....



CODICE  
**BN26WC500210376**

MODELLO  
**BOWBT02**

SERIE  
**REFRIGERATED  
TABLES**

## Technical Information

SPECIFICATION	DATA
MATERIAL	BN26WC500210376
DEFINITION	BOWBT02 R290DX BT PSPD S/P BAR
DIM. WIDTH	1270 mm
DIM. PRODUCTIVITY	700 mm
DIM. HEIGHT	810 mm
NET WEIGHT	80 Kg
VOLUME (net)	0.72009
PACKAGE LENGTH	1320 mm
PACKAGE WIDTH	750 mm
PACKAGING HEIGHT	1060 mm
PACKAGE VOLUME	1,049 m3
GROSS PACKING WEIGHT	102 Kg
STANDARD POWER SUPPLY	220-240V 1N
FREQUENCY	50Hz
ELECTRICAL POWER	0.515 kW
GAS/REFRIGERANT TYPE	R452a
IP GRADE	IPX4
CAPACITY	246

**REFRIGERATED COUNTER GN 1/1 ( 2 DOORS TEMP  
-15/-20°C)**

Project .....

Rev.: .....

Zone: .....


Location: .....



CODICE  
**BN26WC500210376**

MODELLO  
**BOWBT02**

SERIE  
REFRIGERATED  
TABLES



# REFRIGERATED COUNTER GN 1/1 ( 2 DOORS TEMP -15/-20°C)

Project .....  
Rev.: .....  
Zone: .....  
Location: .....



CODICE  
BN26WC500210376

MODELLO  
BOWBT02

SERIE  
REFRIGERATED  
TABLES

## PRODUCT'S RANGE PLUS



Ease of programming and immediate accessibility. The solution for quick and easy use.



Molded cell bottom with rounded edges and removable grid supports for maximum hygiene and loading flexibility.



The temperature uniformity throughout the refrigerated compartment is secured by a patented ventilation system using air channelling, aided by the absence of the evaporator in the compartment.



Full extension drawers with special Filterer stainless steel telescopic slides