

FREEZER COUNTER WITHOUT MOTOR (3 DOORS TEMP -15/-20°C) WITH TOP WITH BACKSPLASH

Project
Rev.:
Zone:
Location:



CODICE
BN26WC602210307

MODELLO
BOWPBT03PA

SERIE
REFRIGERATED
TABLES

GENERAL CHARACTERISTICS

Baron refrigerated tables, all certified for efficiency and quality, guarantee the perfect observation of raw materials, processed delicatessen products, thanks also to an automatic door closing system with magnetic gasket.



TECHNICAL SPECIFICATIONS

Cell bottom printed with rounded corners and removable grid supports for the maximum degree of hygiene and load flexibility. Insulation thickness of 60 mm, made of high-density expanded polyurethane, completely free of CFC. Fully extractable drawers, thanks to special Fullterer telescopic guides in stainless steel. Self-closing door with 100° opening lock. Lower hinge fixed frontally for installation on the plinth.

REFRIGERATION UNIT

Equipped with a remote condensing unit. Out-of-cell evaporator for greater loading convenience

Ducted ventilation system to even out internal temperature

Evaporators with treatment in cataphoresis

CONTROLS, MONITORING, AND SAFETY FEATURES:

Electronic control board with HACCP function

Electric defrost (on predisposed versions)

Automatic condensate water evaporation device

FREEZER COUNTER WITHOUT MOTOR (3 DOORS TEMP -15/-20°C) WITH TOP WITH BACKSPLASH

Project
Rev.:
Zone:
Location:



CODICE
BN26WC602210307

MODELLO
BOWPBT03PA

SERIE
**REFRIGERATED
TABLES**

Technical Information

SPECIFICATION	DATA
MATERIAL	BN26WC602210307
SUPPLY	ELECTRICS
DIM. WIDTH	1735 mm
DIM. PRODUCTIVITY	700 mm
DIM. HEIGHT	950 mm
NET WEIGHT	89 Kg
VOLUME (net)	1.153775
PACKAGE VOLUME	1.415 m3
GROSS PACKING WEIGHT	106 Kg
STANDARD POWER SUPPLY	220-240V 1N
FREQUENCY	50Hz
ELECTRICAL POWER	0.74 kW
GAS/REFRIGERANT TYPE	R452a
IP GRADE	IPX4
CAPACITY	369

FREEZER COUNTER WITHOUT MOTOR (3 DOORS
TEMP -15/-20°C) WITH TOP WITH BACKSPLASH

Project
Rev.:
Zone:
Location:



CODICE
BN26WC602210307

MODELLO
BOWPBT03PA

SERIE
REFRIGERATED
TABLES



FREEZER COUNTER WITHOUT MOTOR (3 DOORS TEMP -15/-20°C) WITH TOP WITH BACKSPLASH

Project
Rev.:
Zone:
Location:



CODICE
BN26WC602210307

MODELLO
BOWPBT03PA

SERIE
REFRIGERATED
TABLES

PRODUCT'S RANGE PLUS



Ease of programming and immediate accessibility. The solution for quick and easy use.



Molded cell bottom with rounded edges and removable grid supports for maximum hygiene and loading flexibility.



The temperature uniformity throughout the refrigerated compartment is secured by a patented ventilation system using air channelling, aided by the absence of the evaporator in the compartment.



Full extension drawers with special Filterer stainless steel telescopic slides