

WOK 1 GAS FIRE 10KW ON OPEN COMPARTMENT

Project
Rev.:
Zone:
Location:



CODICE
CR1015849

MODELLO
Q90PCV/WG610

SERIE
QUEEN 9

GENERAL CHARACTERISTICS

It is the choice of those who need maximum strength and power. Queen9 is distinguished by its 900 mm depth, a 20/10-thick work surface, double-crown burners, and the use of elegant stainless steel with a Scotch Brite finish.

Details that not only offer maximum functionality and aesthetics, but also take into account the practical and ergonomic needs of those who work.

The extreme freedom of composition allows top models to be combined with accessorizable oven and neutral base units, even with hygienic finishes.

With more than 350 models immediately available in the catalog, Queen9 is already ready to start giving its best.

In addition, all equipment that makes up a Queen9 kitchen is certified in compliance with international standards, including CE, GAR, AGA and others.



TECHNICAL SPECIFICATIONS

Stainless steel outer coverings and feet.

Available with 10 kw or 14 kw burners.

Fireplace for heat venting.

Tops with 20/10 thickness with 550x520 mm or 950x520 mm potting.

Right rear exhaust 22 mm in diameter, prepared for ground connection.

Available in compartment or with doors: for the 60-m module, 2 m 30 doors; for the 100-m module, 2 m 50 doors.

In the compartment area, full-width tray for collecting overflow liquids.

Table top with standardised tank and liquid drainage in the rear right-hand corner.

Tray for collecting overflow liquids.

Thanks to the jet-proofing certification (IPX5) obtained through specific tests, knobs and under-knobs can be washed at the end of the working day without compromising functionality and safety.

The front bar is a comfortable foothold for the cook; it keeps a safe distance from the worktop and thus protects against accidental collisions with what is resting on the worktops and at the same time the handles.

WOK 1 GAS FIRE 10KW ON OPEN COMPARTMENT

Project
Rev.:
Zone:
Location:



CODICE
CR1015849

MODELLO
Q90PCV/WG610

SERIE
QUEEN 9

Technical Information

SPECIFICATION	DATA
MATERIAL	CR1015849
DEFINITION	Q90PCV/WG610 WOK GAS M60 10KW A/G
COMMERCIAL LINE	QUEEN
DIM. WIDTH	600 mm
DIM. PRODUCTIVITY	900 mm
DIM. HEIGHT	870 mm
NET WEIGHT	72 Kg
VOLUME (net)	0.47
PACKAGE LENGTH	960 mm
PACKAGE WIDTH	1080 mm
PACKAGING HEIGHT	1100 mm
PACKAGE VOLUME	1,140 m3
GROSS PACKING WEIGHT	85 Kg
GAS POWER	10

WOK 1 GAS FIRE 10KW ON OPEN COMPARTMENT

Project
Rev.:
Zone:
Location:




CODICE
CR1015849

MODELLO
Q90PCV/WG610

SERIE
QUEEN 9

MISURE IN cm - DIMENSIONS IN cm - ABMESSUNGEN IN cm- MESURES EN cm
MEDIDAS EN cm - MATEN IN cm - DIMENSIONES EN cm



Legenda - Legende - Key - Légende - Leyenda - Legenda - Legenda

E	Pressacavo entrata linea elettrica - Stopfbuchse - Electric cable stress relief - Presse étoupe de câble él - Pisacable - Elektrische kabelwartel - Entrada cabo eléctrico	G	Arrivo gas - Gasanschluss - Gas connection - Arrivée gaz - Union de gas - Gasaansluiting - Ligaçao gás EN 10226-1 R 1/2; EN ISO 228-1 G 1/2 (DK)
S	Attacco scarico acqua - Wasserablauf - Water outlet - Vidange de l'eau - Desaguadero - Wateraftapaansluiting - Junção descarga água EN 10226-1 R1	H20	Arrivo acqua - Wasseranschluss - Water inlet - Arrivée eau - Union de água - Wateraansluiting - Junção alimentação água
S1	Scarico vasca - Wannenabflussrohr - Pan outlet - Vidange du bac - Descarga cuba - Water toevoer - Descarga da cuba	A1 =	Calda - Heiss - Warm - Chaude - Caliente - Warm - Morno
S2	Valvola di depressione - Anti-depression valve - Unterdruck ventil - Soupape de dépression - Válvula de depresión - Onderdrukkelep - Válvula de depressão	A2 =	Fredda - Kalt - Cold - Froid - Fria - Koude - Frio
S3	Scarico acqua intercapedine - Wasserablauf Zwischenraum - Jacket water drain Evacuation eau double envelope - Descarga de água interstícios - Afvoer water tussenruimte - Descarga de água na marmitta com Sistema de aquecimento indirecto	L	Rubinetto di livello - Level tap - Wasserhahn - Robinet de niveau - Grifo de nivel - Niveaakraan - Torneira de nivel
S4	Scarico - Abflussrohr - Drain - Tuyau d'évacuation - Tubo de drenaje - Aftapbuis - Tubulação de dreno		

WOK 1 GAS FIRE 10KW ON OPEN COMPARTMENT

Project
Rev.:
Zone:
Location:



CODICE
CR1015849

MODELLO
Q90PCV/WG610

SERIE
QUEEN 9

PRODUCT'S RANGE PLUS



10 kW or 14 kW enameled cast-iron burners removable for easy cleaning.



Table top with standardised tank and liquid drainage in the rear right-hand corner.



Tray for collecting overflow liquids.