

# GN 1/1 PRESERVATION TABLE (4 DOORS TEMP -15/-20°C) WITH TOP

Project .....  
Rev.: .....  
Zone: .....  
Location: .....



CODICE  
BN26KK621210306

MODELLO  
BOKPBT04P

SERIE  
REFRIGERATED  
TABLES

## GENERAL CHARACTERISTICS

Baron refrigerated tables, all certified for efficiency and quality, guarantee the perfect observation of raw materials, processed delicatessen products, thanks also to an automatic door closing system with magnetic gasket.



## TECHNICAL SPECIFICATIONS

Cell bottom printed with rounded corners and removable grid supports for the maximum degree of hygiene and load flexibility. Insulation thickness of 60 mm, made of high-density expanded polyurethane, completely free of CFC. Fully extractable drawers, thanks to special Fullterer telescopic guides in stainless steel. Self-closing door with 100° opening lock. Lower hinge fixed frontally for installation on the plinth.

### REFRIGERATION UNIT

Equipped with a remote condensing unit

Evaporators positioned behind each door pillar to ensure uniform cold distribution

Evaporators with treatment in cataphoresis

### CONTROLS, MONITORING, AND SAFETY FEATURES:

Electronic control board with HACCP function

Electric defrost (on predisposed versions)

# GN 1/1 PRESERVATION TABLE (4 DOORS TEMP -15/-20°C) WITH TOP

Project .....  
Rev.: .....  
Zone: .....  
Location: .....



CODICE  
BN26KK621210306

MODELLO  
BOKPBT04P

SERIE  
REFRIGERATED  
TABLES

## Technical Information

SPECIFICATION	DATA
MATERIAL	BN26KK621210306
SUPPLY	ELECTRICS
DIM. WIDTH	2015 mm
DIM. PRODUCTIVITY	700 mm
DIM. HEIGHT	850 mm
NET WEIGHT	106 Kg
VOLUME (net)	1.198925
PACKAGE VOLUME	1.781 m3
GROSS PACKING WEIGHT	126 Kg
STANDARD POWER SUPPLY	220-240V 1N
FREQUENCY	50Hz
ELECTRICAL POWER	0.955 kW
GAS/REFRIGERANT TYPE	R452a
IP GRADE	IPX4
CAPACITY	492

# GN 1/1 PRESERVATION TABLE (4 DOORS TEMP -15/-20°C) WITH TOP


Project .....  
Rev.: .....  
Zone: .....  
Location: .....



CODICE  
BN26KK621210306


MODELLO  
BOKPBT04P

SERIE  
REFRIGERATED  
TABLES



## Remote unit connections:

- suction Ø8 m
- liquid Ø6 m



	Power cable position & length / Position und Länge des Speisekabels / Posizione e lunghezza cavo alim.
	Refrigerant tubes / Kälteleitungen / Tubi refrigeranti
	Drainage pipe / Ablaufrohr / Tubo scarico
	Electrical components position / Position der elektrischen Komponente / Posizione componenti elettrici

## OKP 4 DOORS GASTRONORM H 660

REFRIGERATED COUNTERS WITHOUT  
COOLING UNIT  
KÜHLTISCHE OHNE KÜHLEINHEIT  
TAVOLI REFRIGERATI PREDISPOSTI  
TABLES REFRIGERÉES SANS GROUPE LOGE  
MESAS REFRIGERADA SIN UNIDAD DE ENFRIAMIENTO

# GN 1/1 PRESERVATION TABLE (4 DOORS TEMP -15/-20°C) WITH TOP

Project .....  
Rev.: .....  
Zone: .....  
Location: .....



CODICE  
BN26KK621210306

MODELLO  
BOKPBT04P

SERIE  
REFRIGERATED  
TABLES


## PRODUCT'S RANGE PLUS



Ease of programming and immediate accessibility. The solution for quick and easy use.



Molded cell bottom with rounded edges and removable grid supports for maximum hygiene and loading flexibility.



The temperature uniformity throughout the refrigerated compartment is secured by a patented ventilation system using air channelling, aided by the absence of the evaporator in the compartment.



Full extension drawers with special Fuller stainless steel telescopic slides