

# GN 1/1 PRESERVATION TABLE ( 2 DOORS TEMP -15/-20°C ) WITH TOP

Project .....  
Rev.: .....  
Zone: .....  
Location: .....



CODICE  
BN26WC600210306

MODELLO  
BOWPBT02P

SERIE  
REFRIGERATED  
TABLES

## GENERAL CHARACTERISTICS

Baron refrigerated tables, all certified for efficiency and quality, guarantee the perfect observation of raw materials, processed delicatessen products, thanks also to an automatic door closing system with magnetic gasket.



## TECHNICAL SPECIFICATIONS

Cell bottom printed with rounded corners and removable grid supports for the maximum degree of hygiene and load flexibility. Insulation thickness of 60 mm, made of high-density expanded polyurethane, completely free of CFC. Fully extractable drawers, thanks to special Fuller telescopic guides in stainless steel. Self-closing door with 100° opening lock. Lower hinge fixed frontally for installation on the plinth.

### REFRIGERATION UNIT

Equipped with a remote condensing unit. Out-of-cell evaporator for greater loading convenience

Ducted ventilation system to even out internal temperature

Evaporators with cathodic treatment

### CONTROLS, MONITORING, AND SAFETY FEATURES:

Electronic control board with HACCP function

Electric defrost (on predisposed versions)

Automatic evaporation device for condensate water

# GN 1/1 PRESERVATION TABLE ( 2 DOORS TEMP -15/-20°C ) WITH TOP

Project .....  
Rev.: .....  
Zone: .....  
Location: .....



CODICE  
**BN26WC600210306**

MODELLO  
**BOWPBT02P**

SERIE  
**REFRIGERATED  
TABLES**

## Technical Information

| SPECIFICATION         | DATA            |
|-----------------------|-----------------|
| MATERIAL              | BN26WC600210306 |
| SUPPLY                | ELECTRICS       |
| DIM. WIDTH            | 1275 mm         |
| DIM. PRODUCTIVITY     | 700 mm          |
| DIM. HEIGHT           | 850 mm          |
| NET WEIGHT            | 74 Kg           |
| VOLUME (net)          | 0.758625        |
| PACKAGE VOLUME        | 1.049 m3        |
| GROSS PACKING WEIGHT  | 88 Kg           |
| STANDARD POWER SUPPLY | 220-240V 1N     |
| FREQUENCY             | 50Hz            |
| ELECTRICAL POWER      | 0.515 kW        |
| GAS/REFRIGERANT TYPE  | R452a           |
| IP GRADE              | IPX4            |
| CAPACITY              | 246             |

**GN 1/1 PRESERVATION TABLE ( 2 DOORS TEMP  
-15/-20°C ) WITH TOP**

Project .....  
Rev.: .....  
Zone: .....  
Location: .....



CODICE  
**BN26WC600210306**

MODELLO  
**BOWPBT02P**

SERIE  
**REFRIGERATED  
TABLES**

# GN 1/1 PRESERVATION TABLE ( 2 DOORS TEMP -15/-20°C ) WITH TOP

Project .....  
Rev.: .....  
Zone: .....  
Location: .....



CODICE  
BN26WC600210306

MODELLO  
BOWPBT02P

SERIE  
REFRIGERATED  
TABLES

## PRODUCT'S RANGE PLUS



Ease of programming and immediate accessibility. The solution for quick and easy use.



Molded cell bottom with rounded edges and removable grid supports for maximum hygiene and loading flexibility.



The temperature uniformity throughout the refrigerated compartment is secured by a patented ventilation system using air channelling, aided by the absence of the evaporator in the compartment.



Full extension drawers with special Fuller stainless steel telescopic slides