

REFRIGERATED TABLE (2 DOORS TEMP -2/+8°C) WITH TOP

Project
Rev.:
Zone:
Location:



CODICE
BN26KK0002103LA

MODELLO
BOK02P

SERIE
REFRIGERATED
TABLES

GENERAL CHARACTERISTICS

Baron refrigerated tables, all certified for efficiency and quality, guarantee the perfect observation of raw materials, processed delicatessen products, thanks also to an automatic door closing system with magnetic gasket.



TECHNICAL SPECIFICATIONS

Cell bottom printed with rounded corners and removable grid supports for the maximum degree of hygiene and load flexibility. Insulation thickness of 60 mm, made of high-density expanded polyurethane, completely free of CFC. Fully extractable drawers, thanks to special Fullterer telescopic guides in stainless steel. Self-closing door with 100° opening lock. Lower hinge fixed frontally for installation on the plinth.

REFRIGERATION UNIT

Evaporators positioned behind each door pillar to ensure uniform cold distribution

Evaporators with cathodic treatment

CONTROLS, MONITORING, AND SAFETY FEATURES:

Electronic control board with HACCP function

Hot gas defrost system (onboard motor versions)

Electric defrost (on predisposed versions)

Automatic evaporation device for condensate water without the need for electrical energy

REFRIGERATED TABLE (2 DOORS TEMP -2/+8°C) WITH TOP

Project
Rev.:
Zone:
Location:



CODICE
BN26KK0002103LA

MODELLO
BOK02P

SERIE
REFRIGERATED
TABLES

Technical Information

SPECIFICATION	DATA
MATERIAL	BN26KK0002103LA
SUPPLY	ELECTRICS
DIM. WIDTH	1275 mm
DIM. PRODUCTIVITY	700 mm
DIM. HEIGHT	850 mm
NET WEIGHT	82 Kg
VOLUME (net)	0.758625
PACKAGE VOLUME	1.049 m3
GROSS PACKING WEIGHT	96 Kg
STANDARD POWER SUPPLY	220-240V 1N
FREQUENCY	50Hz
ELECTRICAL POWER	0.21 kW
GAS/REFRIGERANT TYPE	R134a
IP GRADE	IPX4
CAPACITY	246

REFRIGERATED TABLE (2 DOORS TEMP -2/+8°C) WITH TOP

Project
Rev.:
Zone:
Location:



CODICE
BN26KK0002103LA

MODELLO
BOK02P

SERIE
REFRIGERATED
TABLES



	Power cable position & length / Position und Länge des Speisekabels / Posizione e lunghezza cavo alimentazione
	Refrigerant tubes / Kälteleitungen / Tubi refrigeranti
	Drainage pipe / Abflusshohr / Tubo scarico
	Electrical components position / Position der elektrischen Komponente / Posizione componenti elettrici

OK 2 DOORS
GASTRONORM H 660
REFRIGERATED COUNTERS
KÜHLTISCHE / TAVOLI REFRIGERATI
TABLES REFRIGERÉES
MESAS REFRIGERADAS
GEKOELDE WERKBANKEN
ОХЛАЖДЕННЫЕ ПРИЛАВКИ

REFRIGERATED TABLE (2 DOORS TEMP -2/+8°C) WITH TOP

Project
Rev.:
Zone:
Location:



CODICE
BN26KK0002103LA

MODELLO
BOK02P

SERIE
REFRIGERATED
TABLES

PRODUCT'S RANGE PLUS



Evaporators placed behind each door pillar to ensure uniformity in cold distribution.



Ease of programming and immediate accessibility. The solution for quick and easy use.



Capacitor protected by filters to ensure optimal operation over time.



Molded cell bottom with rounded edges and removable grid supports for maximum hygiene and loading flexibility.



Full extension drawers with special Filterer stainless steel telescopic slides