

ELECTRIC FRYER 1 BASIN 22 L - WITH 2 BASKET KIT

Project
Rev.:
Zone:
Location:



CODICE
CR1353799T4W

MODELLO
QT90FRI/E422-T4W

SERIE
BARON 4.0

GENERAL CHARACTERISTICS

From the solid foundation of Baron tradition, comes the new Queen 4.0 kitchen, even more practical, more accessorized, more technological.

An evolution in the field of professional kitchens.

Queen 4.0 is perfectly designed in detail to speed up and simplify every task of preparation, cooking, tidying up, and cleaning in the kitchen, and stand by you every day as a true ally in your work.



TECHNICAL SPECIFICATIONS

Stainless steel outer coatings and feet.

Height of the work surface adjustable from 840 to 900mm.

Tops with a thickness of 2 mm.

AISI 18/10 stainless steel tanks with cold zone and foam expansion zone.

Oil drain taps.

Oil drip pans on request.

Safety thermostat (230°C) against excessive oil overtemperatures.

Heating by means of an AISI 304 stainless steel armoured heating element inside the tank and rotatable by more than 90° in the 22lt tank version.

Fully removable heating element in the 10 and 15-liter tank version.

Thanks to the jet-proofing certification (IPX5) obtained through specific tests, knobs and under-knobs can be washed at the end of the working day without compromising functionality and safety.

The front bar is a comfortable foothold for the cook; it keeps a safe distance from the worktop and thus protects against accidental collisions with what is resting on the worktops and at the same time the handles.

ELECTRIC FRYER 1 BASIN 22 L - WITH 2 BASKET KIT

Project
Rev.:
Zone:
Location:



CODICE
CR1353799T4W

MODELLO
QT90FRI/E422-T4W

SERIE
BARON 4.0

Technical Information

SPECIFICATION	DATA
MATERIAL	CR1353799T4W
DEFINITION	Q90FRI/E422-T4W FRIG.EL. 1V 22LT IOT M40
COMMERCIAL LINE	QUEEN
SUPPLY	ELECTRICS
DIM. WIDTH	400 mm
DIM. PRODUCTIVITY	900 mm
DIM. HEIGHT	850 mm
NET WEIGHT	0 Kg
VOLUME (net)	0,306
PACKAGE LENGTH	440 mm
PACKAGE WIDTH	980 mm
PACKAGING HEIGHT	500 mm
PACKAGE VOLUME	0,216 m3
GROSS PACKING WEIGHT	0 Kg
STANDARD POWER SUPPLY	380-415V 3N
FREQUENCY	50/60 Hz
ELECTRICAL POWER	18,000 kW
IP GRADE	IPX4
CAPACITY	22 litri

ELECTRIC FRYER 1 BASIN 22 L - WITH 2 BASKET KIT

Project
Rev.:
Zone:
Location:




CODICE
CR1353799T4W

MODELLO
QT90FRI/E422-T4W

SERIE
BARON 4.0

MISURE IN cm - DIMENSIONS IN cm - ABMESSUNGEN IN cm- MESURES EN cm
MEDIDAS EN cm - MATEN IN cm - DIMENSIONES EN cm



Legenda - Legende - Key - Légende - Leyenda - Legenda - Legenda			
E	Pressacavo entrata linea elettrica - Stopfbuchse - Electric cable stress relief - Presse étoupe de câble él - Pisacable - Elektrische kabelwartel - Entrada cabo eléctrico	G	Arrivo gas - Gasanschluss - Gas connection - Arrivée gaz - Union de gas - Gasaansluiting - Ligação gás
S	Attacco scarico acqua - Wasserablauf - Water outlet - Vidange de l'eau - Desaguadero - Wateraftapaansluiting - Junção descarga água	H20	Arrivo acqua - Wasseranschluss - Water inlet - Arrivée eau - Union de água - Wateraansluiting - Junção alimentação água
S1	Scarico vasca - Wannenabflussrohr - Pan outlet - Vidange du bac - Descarga cuba - Water toevoer - Descarga da cuba	A1 =	Calda - Heiss - Warm - Chaude - Caliente - Warm - Morno
S2	Valvola di depressione - Anti-depression valve - Unterdruck ventil - Soupape de dépression - Válvula de depresión - Onderdrukklep - Válvula de depressão	A2 =	Fredda - Kalt - Cold - Froid - Fria - Koude - Frio
S3	Scarico acqua intercapedine - Wasserablauf Zwischenraum - Jacket water drain Evacuation eau double envelope - Descarga de água interstícios - Afvoer water tussenruimte - Descarga de água na marmitta com Sistema de aquecimento indirecto	L	Rubinetto di livello - Level tap - Wasserhahn - Robinet de niveau - Grifo de nivel - Niveaakraan - Torneira de nível
S4	Scarico - Abflussrohr - Drain - Tuyau d'évacuation - Tubo de drenaje - Aftapbuis - Tubulação de dreno		

ELECTRIC FRYER 1 BASIN 22 L - WITH 2 BASKET KIT

Project
Rev.:
Zone:
Location:



CODICE
CR1353799T4W

MODELLO
QT90FRI/E422-T4W

SERIE
BARON 4.0

PRODUCT'S RANGE PLUS



Data collection, operation monitoring, remote control are just some of the possibilities that connectivity puts at your disposal.



Thanks to the jet-proofing certification (IPX5) obtained through specific tests, knobs and under-knobs can be washed at the end of the working day without compromising functionality and safety.



The front bar is a comfortable foothold for the cook; it keeps a safe distance from the worktop and thus protects against accidental collisions with what is resting on the worktops and at the same time the handles.

ELECTRIC FRYER 1 BASIN 22 L - WITH 2 BASKET KIT

Project
Rev.:
Zone:
Location:



CODICE
CR1353799T4W

MODELLO
QT90FRI/E422-T4W

SERIE
BARON 4.0

ACCESSORIES

CODE	MODELLO	DESCRIZIONE
CR1357499	4.0IOTPRO	PRO Subscription - Cloud
CR1357479	4.0IOTENTRY	ENTRY Subscription - Cloud
CR1353969	QCF22/23P	STAINLESS STEEL BASKET FOR FRYERS 22/23P LT
CR1353979	QCF22/23	22/23 L STAINLESS STEEL BASKET FOR FRYERS
CR0997189	9BRO	OIL PAN
BN418031940080	CF 12M	FRYING TANK LID
BN418031940150	GFF15	BOTTOM GRID FRYER 15 L
BN418031940180	CF15	FRYER BASKET 15 L
BN418031940190	CF15P	SMALL BASKET FOR FRYER 15 LT