

GENERAL CHARACTERISTICS

From the solid foundation of Baron tradition, comes the new Queen 4.0 kitchen, even more practical, more accessorized, more technological.

An evolution in the field of professional kitchens.

Queen 4.0 is perfectly designed in detail to speed up and simplify every task of preparation, cooking, tidying up, and cleaning in the kitchen, and stand by you every day as a true ally in your work.



TECHNICAL SPECIFICATIONS

AISI 304 work surface and dashboard.

"Thermoblock" heating elements: heating elements, armored included in an aluminum casting with high heat resistance.

Equipped with programmable automatic water loading.

Can be used in 7 functionalities: fry top / BRATT PAN / pasta cooker / slow cooker / steaming / kettle / bain-marie.

Double-walled lid without perimeter seal.

Two USB outputs located under the dashboard (compartment area) for storing recipes and updating software.

Control of the firings by means of a probe at the core.

Gastronorm-sized tub.

Thanks to the jet-proofing certification obtained through specific tests, knobs and under-knobs can be washed at the end of the working day without compromising functionality and safety.

The front bar is a comfortable foothold for the cook; it keeps a safe distance from the worktop and thus protects against accidental collisions with what is resting on the worktops and at the same time the handles.

CODICE
CR1014739T4WMODELLO
Q70MA/E800-T4WSERIE
BARON 4.0

Technical Information

SPECIFICATION	DATA
MATERIAL	CR1014739T4W
DEFINITION	Q70MA/E800 MULTI COOKER EL.TALENT BARON
COMMERCIAL LINE	DIAMANTE
SUPPLY	ELECTRICS
DIM. WIDTH	800 mm
DIM. PRODUCTIVITY	700 mm
DIM. HEIGHT	870 mm
NET WEIGHT	0 Kg
VOLUME (net)	0.244
PACKAGE LENGTH	860 mm
PACKAGE WIDTH	1020 mm
PACKAGING HEIGHT	1150 mm
PACKAGE VOLUME	1,009 m3
GROSS PACKING WEIGHT	0 Kg
STANDARD POWER SUPPLY	380-415V 3N
FREQUENCY	50-60 Hz
ELECTRICAL POWER	10 kW
IP GRADE	IPX4


TALENT SLIM L 800

CODICE CR1014739T4W	MODELLO Q70MA/E800-T4W	SERIE BARON 4.0
------------------------	---------------------------	--------------------

Project
Rev.:
Zone:
Location:



MISURE IN cm - DIMENSIONS IN cm - ABMESSUNGEN IN cm- MESURES EN cm
MEDIDAS EN cm - MATEN IN cm - DIMENSIONES EN cm



Legenda - Legende - Key - Légende - Leyenda - Legenda - Legenda	
E Pressacavo entrata linea elettrica - Stopfbuchse - Electric cable stress relief - Presse étoupe de câble él - Pisacable - Elektrische kabelwartel - Entrada cabo eléctrico	G Arrivo gas - Gasanschluss - Gas connection - Arrivée gaz - Union de gas - Gasaansluiting - Ligação gás
S Attacco scarico acqua - Wasserablauf - Water outlet - Vidange de l'eau - Desaguadero - Wateraftapaansluiting - Junção descarga água UNI EN 10226-1 R 1"	H20 Arrivo acqua - Wasseranschluss - Water inlet - Arrivée eau - Union de agua - Wateraansluiting - Junção alimentação água
S1 Scarico vasca - Wannenabflussrohr - Pan outlet - Vidange du bac - Descarga cuba - Water toevoer - Descarga da cuba	A1 = Calda - Heiss - Warm - Chaude - Caliente - Warm - Morno A2 = Fredda - Kalt - Cold - Froid - Fria - Koude - Frio EN ISO 228-1 G3/4
S2 Valvola di depressione - Anti-depression valve - Unterdruck ventil - Soupape de dépression - Válvula de depresi3n - Onderdrukplep - Válvula de depress3o	L Rubinetto di livello - Level tap - Wasserhahn - Robinet de niveau - Grifo de nivel - Niveaakraan - Torneira de nível
S3 Scarico acqua intercapedine - Wasserablauf Zwischenraum - Jacket water drain Evacuation eau double envelope - Descarga de agua intersticios - Afvoer water tussenruimte - Descarga de água na marmita com Sistema de aquecimento indirecto	
S4 Scarico - Abflussrohr - Drain - Tuyau d'évacuation - Tubo de drenaje - Aftapbuis - Tubulaç3o de dreno	

PRODUCT'S RANGE PLUS



Basin for draining the cooked product into the tank. Guaranteed cleanliness of the station and ease in transporting products.




Control of cooking by core probe.



Automatic water filling with the possibility of programming litres.



Mains water drain with overflow drain and basin drain hole with sealing plug.



Easy to understand and use Touch Screen control panel. Possibility of storing personal recipes.

TALENT SLIM L 800

Project
Rev.:
Zone:
Location:



CODICE
CR1014739T4W

MODELLO
Q70MA/E800-T4W

SERIE
BARON 4.0

ACCESSORIES

CODE	MODELLO	DESCRIZIONE
CR1200179	CAMCF	Lid for steamer use
CR1200169	GFMCF	Tank bottom grid
CR1200159	CPC1/3MCF	GN1/3 basket for pasta cooker
CR1200119	TSCMCF	Frame for slow cooking
CR0956330	SDXP	Shovel
CR0999069	CRLMCF	Trolley for multifunctional
CR1200149	CV1/3MCP	GN1/3 steamer basket 160x280x115(H)cm