

REFRIGERATED CABINET - TEMP. -2° +8° / -25°-15° - 700 LT -2+8°C/-25-15°C 2 1/2 DOORS - GAS R290

Project
Rev.:
Zone:
Location:



CODICE
BN20SC46BM35

MODELLO
BEV35/35TNNBT

SERIE
REFRIGERATED
CABINETS

GENERAL CHARACTERISTICS

One-piece construction with AISI304 stainless steel interior and exterior finish.
Insulation thickness 85 mm high density.
Dashboard openable for easy periodic maintenance (condenser cleaning).
External back and sternum base in pre-painted steel.
Magnetic gasket on all four sides and counter-magnet on the gasket rebates.
Ergonomic full-height handle recessed into the front of the door for easy opening in any type of installation.
Inner compartment with 26-position moulded sides, 3 Rilsan GN2/1 grids included.
Foamed engine compartment sides for better soundproofing and greater strength.
Hot gas defrosting and defrost water disposal system without energy consumption.
Indirect ventilation thanks to the full-height ducting system for optimal air circulation and uniform temperature distribution.
Environmentally friendly refrigerant R290



TECHNICAL SPECIFICATIONS

Internal and external in stainless steel.
Sides stamped (excluding models 35/35 and 70/70).
Wall insulation of 83 mm with CFC-free polyurethane.
Dashboard openable for easy periodic maintenance (condenser cleaning).
Basic and intuitive easy control.
Cell interior with rounded corners for easy cleaning.
Height-adjustable 150 mm steel feet.

Automatic defrost with resistance and condensate water dissipation through hot gas.
Self-closing doors with hinges.
Standard lighting and lock for cell illumination.
Prepared for placement on plinth.
Buffer monoblock, external to the cell, with forced ventilation from top to bottom.

REFRIGERATED CABINET - TEMP. -2° +8° / -25°-15° - 700
LT -2+8°C/-25-15°C 2 1/2 DOORS - GAS R290

Project
Rev.:
Zone:
Location:



CODICE
BN20SC46BM35

MODELLO
BEV35/35TNNBT

SERIE
**REFRIGERATED
CABINETS**

Technical Information

| SPECIFICATION | DATA |
|-----------------------|-------------------|
| MATERIAL | BN20SC46BM35 |
| SUPPLY | ELECTRICS |
| DIM. WIDTH | 700 mm |
| DIM. PRODUCTIVITY | 830 mm |
| DIM. HEIGHT | 2080 mm |
| NET WEIGHT | 146 Kg |
| PACKAGE LENGTH | 860 mm |
| PACKAGE WIDTH | 760 mm |
| PACKAGING HEIGHT | 2220 mm |
| PACKAGE VOLUME | 1.45 m3 |
| GROSS PACKING WEIGHT | 159 Kg |
| STANDARD POWER SUPPLY | 220-240V 1N |
| ELECTRICAL POWER | 0.91 kW |
| GAS/REFRIGERANT TYPE | R290 |
| REFRIGERATION POWER | 294+664 |
| CELL SIZE | 2X 550X710X695 MM |
| CAPACITY | 282+282 LT |

REFRIGERATED CABINET - TEMP. -2° +8° / -25°-15° - 700

LT -2+8°C/-25-15°C 2 1/2 DOORS - GAS R290

Project
 Rev.:
 Zone:
 Location:



CODICE
BN20SC46BM35

MODELLO
BEV35/35TNNBT

SERIE
REFRIGERATED
CABINETS



REFRIGERATED CABINET - TEMP. -2° +8° / -25°-15° - 700
LT -2+8°C/-25-15°C 2 1/2 DOORS - GAS R290

Project
Rev.:
Zone:
Location:



CODICE
BN20SC46BM35

MODELLO
BEV35/35TNNBT

SERIE
REFRIGERATED
CABINETS

PRODUCT'S RANGE PLUS



The temperature is constantly adjusted and controlled through the simple and intuitive Digital Display.



Optimisation of air circulation flows inside the cell thanks to the rear conveyor. Optimum air distribution under all cell load conditions.



Thanks to the R290 gas supplied as standard for all available versions, Olis guarantees care and sustainability in all aspects of its product development.



Moulded grid support guides. Cell with large load capacity, easy to clean thanks to the moulded grid guides. The internal volume of the cell increases by up to 30 litres compared to equivalent products on the market.



Fully radiused cell bottom.