

# STORAGE TABLE OR GN 1/1 ( 2 DOORS TEMP -15/-20°C ) TOP WITH SPLASHBACK

Project .....  
Rev.: .....  
Zone: .....  
Location: .....



CODICE  
**BN26KK5002103LB**

MODELLO  
**BOKBT02PA**

SERIE  
**REFRIGERATED  
TABLES**

## GENERAL CHARACTERISTICS

Baron refrigerated tables, all certified for efficiency and quality, guarantee the perfect observation of raw materials, processed delicatessen products, thanks also to an automatic door closing system with magnetic gasket.



## TECHNICAL SPECIFICATIONS

Cell bottom printed with rounded corners and removable grid supports for the maximum degree of hygiene and load flexibility. Insulation thickness of 60 mm, made of high-density expanded polyurethane, completely free of CFC. Fully extractable drawers, thanks to special Fullterer telescopic guides in stainless steel. Self-closing door with 100° opening lock. Lower hinge fixed frontally for installation on the plinth.

### REFRIGERATION UNIT

Evaporators positioned behind each door pillar to ensure uniform cold distribution

Evaporators with treatment in cataphoresis

### CONTROLS, MONITORING, AND SAFETY FEATURES:

Electronic control board with HACCP function

Hot gas defrost system (onboard motor versions)

Electric defrost (on predisposed versions)

Automatic evaporation device for condensate water without the need for electrical energy

# STORAGE TABLE OR GN 1/1 ( 2 DOORS TEMP -15/-20°C ) TOP WITH SPLASHBACK

Project .....  
Rev.: .....  
Zone: .....  
Location: .....



CODICE  
**BN26KK5002103LB**

MODELLO  
**BOKBT02PA**

SERIE  
**REFRIGERATED  
TABLES**

## Technical Information

| SPECIFICATION         | DATA            |
|-----------------------|-----------------|
| MATERIAL              | BN26KK5002103LB |
| SUPPLY                | ELECTRICS       |
| DIM. WIDTH            | 1275 mm         |
| DIM. PRODUCTIVITY     | 700 mm          |
| DIM. HEIGHT           | 950 mm          |
| NET WEIGHT            | 88 Kg           |
| VOLUME (net)          | 0.847875        |
| PACKAGE LENGTH        | 1320 mm         |
| PACKAGE WIDTH         | 750 mm          |
| PACKAGING HEIGHT      | 1060 mm         |
| PACKAGE VOLUME        | 1,049 m3        |
| GROSS PACKING WEIGHT  | 102 Kg          |
| STANDARD POWER SUPPLY | 220-240V 1N     |
| FREQUENCY             | 50Hz            |
| ELECTRICAL POWER      | 0.49 kW         |
| GAS/REFRIGERANT TYPE  | R452a           |
| IP GRADE              | IPX4            |
| CAPACITY              | 246             |

# STORAGE TABLE OR GN 1/1 ( 2 DOORS TEMP -15/-20°C ) TOP WITH SPLASHBACK

Project .....  
Rev.: .....  
Zone: .....  
Location: .....



CODICE  
BN26KK5002103LB

MODELLO  
BOKBT02PA

SERIE  
REFRIGERATED  
TABLES



|      |  |
|------|--|
| 4 mt | Power cable position & length / Position und Länge des Speisekabels / Posizione e lunghezza cavo alimentazione |
|      | Refrigerant tubes / Kälteleitungen / Tubi refrigeranti   |
|      | Drainage pipe / Abflusrohr / Tubo scarico  |
|      | Electrical components position / Position der elektrischen Komponente / Posizione componenti elettrici         |

**OK 2 DOORS**  
**GASTRONORM H 660**  
REFRIGERATED COUNTERS  
KÜHLTISCHE / TAVOLI REFRIGERATI  
TABLES REFRIGERÉES  
MESAS REFRIGERADAS  
GEKOELDE WERKBANKEN  
ОХЛАЖДЕННЫЕ ПРИЛАВКИ

# STORAGE TABLE OR GN 1/1 ( 2 DOORS TEMP -15/-20°C ) TOP WITH SPLASHBACK

Project .....  
Rev.: .....  
Zone: .....  
Location: .....



CODICE  
BN26KK5002103LB

MODELLO  
BOKBT02PA

SERIE  
REFRIGERATED  
TABLES

## PRODUCT'S RANGE PLUS



Evaporators placed behind each door pillar to ensure uniformity in cold distribution.



Ease of programming and immediate accessibility. The solution for quick and easy use.



Capacitor protected by filters to ensure optimal operation over time.



Molded cell bottom with rounded edges and removable grid supports for maximum hygiene and loading flexibility.



Full extension drawers with special Filterer stainless steel telescopic slides